

#### Better chemistry. Better business.

Hubbard-Hall Inc. • 563 South Leonard Street, Waterbury, CT 07608 • HubbardHall.com • 800-648-3412

### **Product Bulletin**

Product Name: Copperbrite NI Product Code:2380010 Revision Date: October 14, 2020

# Copperbrite NI

Copperbrite NI is a liquid acid product, free of chromates, nitrate/nitrites, and peroxides. Copperbrite NI was developed to brighten and descale copper and brass alloys in an immersion, tumbling, or vibratory mill operation.

### **Features & Benefits**

Non-fuming	Less corrosive/Longer
	equipment life
Un-inhibited	Aggressive annealing scale
	removal
Versatile	Can be used as deoxidizer or
	burnish compound
	Can be used on most copper
	alloys

# **Typical Applications**

- Part on part burnishing in oblique barrel operations
- Descaling of copper alloys
- Activating nickel plate prior to re-plating

# **Operating Conditions**

Concentration	10% – 50%
Operating temperature	Ambient – 140°F (max)
Immersion time	20 – 60 sec
Agitation	Work or solution agitation is beneficial
Equipment	316 Stainless, PVC, polypropylene
Heating	316 Stainless coils or heaters or Teflon









#### Better chemistry. Better business.

Hubbard-Hall Inc. • 563 South Leonard Street, Waterbury, CT 07608 • HubbardHall.com • 800-648-3412

**Product Bulletin** 

Product Name: Copperbrite NI Product Code:2380010 Revision Date: October 14, 2020

Copperbrite NI solution will not generate any heat when it is being operated; consequently, there will be no need for any external cooling. However, for some specific applications, heating of the solution may be necessary.

NOTE: We suggest that the operating temperature be maintained no higher than 120° when the concentration of the Copperbrite NI is at 40 to 50% (vol).

#### Suggested Operating Procedures:

- The parts or work should be alkaline cleaned prior to immersion in the Copperbrite NI solution.
- Heavily scaled or oxidized parts should be processed through a mineral acid pickle
  prior to immersion in Copperbrite NI solution. Even though Copperbrite NI solutions
  will dissolve light scale, it is recommended because oxide scale on parts will vary in
  thickness from part to part. Dissolving the scale in a mineral acid prior to immersion in
  the Copperbrite NI solution will yield a uniformly bright surface.
- Mild work or solution agitation is beneficial.
- To activate nickel plate, use at 5 % by volume, room temperature for 1 to 2 minutes immersion.

### **Titration Method**

- 1. Pipette 10 mL of sample and place in a 250 mL Erlenmeyer flask and add 50 mL of distilled water.
- 2. Add 10 mL 6 N Hydrochloric Acid and 10 mL 15% Potassium Iodide solution and swirl.
- 3. Place flask in the dark for 15 minutes.
- 4. Add 10 mL 0.2% stabilized starch solution.
- 5. Titrate with 0.1 N Sodium Thiosulfate until solution turns clear (no longer blue) and remains clear for 60 seconds.
- 6. Record mL used.

Calculation

Concentration =  $mL 0.1N Na_2S_2O_3 \times 0.58$ 

# **Waste Disposal**

Discharge to a disposal system. In order to be completely informed on the latest regulations for your area, please contact the local authorities.









#### Better chemistry. Better business.

Hubbard-Hall Inc. • 563 South Leonard Street, Waterbury, CT 07608 • HubbardHall.com • 800-648-3412

#### **Product Bulletin**

Product Name: Copperbrite NI Product Code:2380010 Revision Date: October 14, 2020

### **Caution**

Copperbrite NI is an acidic product and should be handled accordingly. Avoid skin, eye and oral contact. Wear protective clothing, gloves and goggles when handling the product. Flush exposed areas immediately with clean, cold water. Contact a doctor immediately in case of injury.

WARRANTY: THE QUALITY OF THIS PRODUCT IS GUARANTEED ON SHIPMENT FROM OUR PLANT. IF THE USE RECOMMENDATIONS ARE FOLLOWED, DESIRED RESULTS WILL BE OBTAINED. SINCE THE USE OF OUR PRODUCTS IS BEYOND OUR CONTROL, NO GUARANTEE EXPRESSED OR IMPLIED IS MADE AS TO THE EFFECTS OF SUCH USE, OR THE RESULTS TO BE OBTAINED.

# Our people. Your problem solvers.

For more information on this process please call us at 1-800-648-3412

or techservice@hubbardhall.com











